

CALL-ROUTING MECHANISM FOR AUTOMATICALLY PERFORMING  
NUMBER SUBSTITUTION IN AN INTEGRATED ACCESS DEVICE

FIELD OF THE INVENTION

09921047-101601

The present invention relates in general to  
5 communication systems, and is particularly directed to a  
called telephone number substitution mechanism, that is  
incorporatable into the call-routing software employed by  
the microcontroller of a customer premises-installed  
digital communication device, such as an integrated  
10 access device (IAD) through which time division  
multiplexed (TDM) and packetized voice and data services  
are supplied to a customer site. This called number  
substitution mechanism is operative to automatically  
selectively modify the digits of an original (dialed)  
15 telephone number, as necessary, to conform with the  
connectivity establishment requirements of the  
communication link serving the destination device, and  
thus enable the call to reach the destination device.

BACKGROUND OF THE INVENTION

20 Digital communication techniques, including but not  
limited to time division multiplexed (TDM), digital  
subscriber loop (DSL), and packetized data-based schemes,  
enable communication service providers to deliver  
multiple types of digital signalling services to various  
25 customer premises equipments. For example, to transport

00981047-101601

packetized voice and data, the service provider may  
deploy several different devices, such as asynchronous  
transfer mode (ATM) switches, digital subscriber line  
access multiplexers (DSLAMs) and voice gateways, in the  
5 signal transport path from a central office to a customer  
premises-resident device (e.g., IAD).

Since the customer premises device is usually  
customer-purchased and installed, the service provider  
does not participate in the customer's choice of what is  
10 connected to the link. Still, in order to provide its  
intended connectivity functionality between customer  
premises equipment and the public switched telephone  
network (PSTN), it is necessary that the device's  
supervisory communications controller conform with the  
15 telephone number dialing scheme employed by the network  
service provider and also that used by the customer  
premises equipment.

Rather than having to reprovision the data terminal  
equipment or the PSTN switch - a costly and time-  
20 consuming exercise - for optimal flexibility, it would be  
desirable to provide the user with the capability of  
modifying (e.g., removing, adding, replacing or  
substituting) digits of the original number. This would  
provide for various operational benefits, such as switch  
25 by-pass capability, and also avoid the need to  
reprovisioning attached customer premises or PSTN  
equipment.

09981047-101501

Unfortunately, the customer is usually technically unsophisticated and accustomed to doing nothing more than performing a 'plug-and-play' exercise, so that any change to initial hardware or software parameters constitutes a major hurdle to the successful deployment of a desired service or equipment modification. Indeed, experience has revealed that a very large majority of customers will burden the equipment supplier and/or the service provider with a request for technical support, in the course of configuring or reconfiguring their equipment, regardless of whether the service provider has correctly supplied the information required.

#### SUMMARY OF THE INVENTION

In accordance with the invention, the ability to adapt the customer's device to variations in number dialing schemes is readily accomplished by a number substitution mechanism executable by the call-routing software employed by the device's microcontroller, through which digital communication service (such as time division multiplexed and packetized voice) is deliverable to a customer site.

Pursuant to a preferred but non-limiting embodiment, the call-routing routine employed by the device communications controller, such as the switch board of an IAD's communications controller, is augmented to incorporate one or more number substitution templates associated with various connectivity paths for the

09981047-101501

communication ports of the device. Each number substitution template is configured to automatically selectively modify one or more digits of an original telephone number, as necessary, to produce a telephone  
5 number that conforms with the call connectivity requirements of the communication link serving the destination device, and thereby enable a call to reach that destination device.

According to the invention, when the digits of an  
10 original number are received by the device (e.g., IAD), the call-routing routine will call up from memory a prescribed number substitution template associated with the port to which the number is coupled. In preparation for comparing the digits of the original number with  
15 those of the accessed template, a plurality of comparison table fields are loaded with initialization values.

One of these fields - a "best\_match\_entry" field - is initially reset or cleared. The "best\_match\_entry" field is used to determine whether the originally  
20 received number is to be replaced by a number in the substitution template; if so, this field also specifies which of those numbers is to be substituted for the originally received number. If not, there is no number replacement, and the originally received number is  
25 forwarded, 'as is' or unmodified.

A second, "this\_entry" field is initially loaded with a first potential substitution number listed in the accessed template. The "this\_entry" field is used in the

course of stepping through and comparing digits of the received number with those of the respective substitution number entries of the template. A third "number" field is loaded with the originally received number. At the  
5 conclusion of the routine, it is the contents of this "number" field that are forwarded as the output number.

Selected digits of the template number in the "this\_entry" field are then compared with selected digits of the originally received number to determine whether  
10 the currently examined template number more closely matches the originally received number than any previous entry. If the first comparison entry from the number substitution template matches the originally received number, then the contents of the "best\_match\_entry" field  
15 are replaced with the number currently written into the "this\_entry" field, and the "this\_entry" field is loaded with the next entry in the template. The contents of the "this\_entry" field are then examined to determine whether the last entry in the number substitution template has  
20 been reached. If not, the routine loops back and proceeds to step through the entirety of the template number substitution list.

As long as one of the potential substitute numbers in the template matches that of the original number (as  
25 stored in the "number" field), a number substitution will be carried out and the contents of the "best\_match\_entry" field substituted for the originally received number contents of the "number" field. This new or replacement

number is then forwarded to the associated IAD output port.

However, if no potential substitute number in the template has at least one digit that matches that of the original number, the "best\_match\_entry" field will still be in its originally cleared condition at the end of the examination of the entire template list; in this event, the originally received number will be forwarded to the associated IAD output port.

Because the number substitution mechanism of the invention is software-based, it provides considerable flexibility in processing the digits of an originally received number and the replacement digits of a substitute number. For example, the invention need not compare all of the digits of the two numbers. Moreover, the number of digits in the originally received number need not be the same as the total number of digits of the template substitute number that is to be forwarded to a downstream path. Either number could have more or less digits than the other. In addition, a substitute number entry may include one or more control flags, such as pause 'commas' embedded with the number contents of the template, that provide for staggered transmission or 'fragmented' transport of the contents substitute number.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 diagrammatically illustrates a reduced complexity example of a digital telecommunication

network, having a communication link coupled from a public switched telephone network to an integrated access device serving customer premises equipment, and incorporating the number substitution mechanism of the present invention; and

Figure 2 is a flow chart of the automated number substitution mechanism of the present invention.

#### DETAILED DESCRIPTION

Before describing in detail the automated number substitution mechanism in accordance with the present invention, it should be observed that the invention resides primarily in a prescribed communication link establishment mechanism, that is embedded in the communications call-routing control software employed by the supervisory communications controller of a digital communication device, such as an integrated access device. Consequently, the invention has been illustrated in the drawings in readily understandable block diagram and associated flow chart format, which show only those specific details that are pertinent to the present invention, so as not to obscure the disclosure with details which will be readily apparent to those skilled in the art having the benefit of the description herein. Thus, the block diagram and flow chart illustrations are primarily intended to illustrate the major components of the invention in a convenient functional grouping,

whereby the present invention may be more readily understood.

Figure 1 is a reduced complexity diagrammatically illustration of the interconnection of customer premises-  
5 installed digital communication unit 10, such as an integrated access device (IAD) as a non-limiting example, serving various customer premises equipments (CPEs), for example, a telephone 12 and a private branch exchange 14, via a digital communication link 16 of a communication  
10 service provider, through which access to a PSTN 18 (serving a remote customer phone 19) is provided. As a non-limiting example, the digital communication unit 10 may comprise an Atlas 550 IAD, manufactured by Adtran Corp., Huntsville, Alabama. It should be observed,  
15 however, that the invention is not limited to use with this or any other communication device, but is intended as an augmentation to the communication supervisory control mechanisms employed in communication devices supplied from a variety of telecommunication equipment  
20 manufacturers.

To provide call connectivity between the network and customer premises equipment, the device's communications controller contains what is customarily termed a 'switch board' software module 20. This switch board software  
25 module is operative to route outgoing and incoming calls to respective ones of the device's communication ports, in accordance with original (e.g., dialed destination) number information contained in the call. The port-

09981047-101501



steering operation of the call-routing switch board is typically governed by initialization parameters with which the device and the CPE equipment have been provisioned at the time of installation and set-up.

5 Pursuant to the invention, this call-routing routine is augmented to include one or more number substitution templates or filters associated with various connectivity paths from the switch board to the communication ports of the device, including those on the customer premises side  
10 and the network side. In the reduced complexity example shown in Figure 1, switch board 20 is shown as having three respective number substitution templates or filters 22, 24 and 26, associated with ports 32, 34 and 36, that couple to the telephone 12, PBX 14 and network link 16  
15 with the PSTN.

Each number substitution template serves to automatically selectively modify or replace the digits of an original or incoming (e.g., dialed) telephone number, as necessary, to produce a telephone number that conforms  
20 with call connectivity requirements of the communication link serving the destination device, and thereby enables a call to reach that destination device.

Respective steps of the number substitution routine carried out by the call-routing augmentation scheme of  
25 the invention are shown in Figure 2. In accordance with this routine, when the digits of an original number are presented to the device (either from the network or CPE equipment), they are received and captured at initial

step 201. In response to receipt of this original number, the routine will call up from memory a prescribed number substitution template that is associated with the port to which the number is applied, and one or more comparison  
5 or input entries of which are to be compared with the received number, to determine whether any associated output or substitution entry is to be substituted for the original number. As will be described, the routine accommodates for one or more 'wild card' digits, to  
10 provide for a 'best match' of less than all digits of the received number.

In step 202, prior to comparing digits of the original number with input or comparison entries of the accessed number substitution template, plural comparison  
15 table fields of the number substitution routine are loaded with initialization values. In particular, a first, "best\_match\_entry" field is reset/cleared or set to null (all zeroes). As will be described, upon completion of the call substitution routine, the  
20 "best\_match\_entry" field will indicate whether or not the originally received number is to be replaced by a substitution number listed in the output or replacement list of the template and, if so, which replacement entry is to be substituted for the original number.

25 After stepping through all of the comparison entries of the template, if the "best\_match\_entry" field still remains a null, it is concluded that there is to be no number substitution or replacement, and the originally

09981047 101501

received number is forwarded 'as is' or unmodified. On the other hand, if the contents of the "best\_match\_entry" are not a null after stepping through all of the comparison entries of the template, then the substitution  
5 number of the substitution template currently associated with the "best\_match\_entry" will be substituted for the originally received number.

In addition to clearing the "best\_match\_entry" field, step 202 also loads a second, "this\_entry" field  
10 with a first or initial comparison entry from the accessed template. The "this\_entry" field is used in the course of stepping through and comparing the digits of the received number with those of respective comparison entries of the number substitution template. Step 202  
15 also loads a third "number" field with the originally received number. It is the contents of this "number" field (which will either be a replacement number or the originally received number) that are forwarded as the output number at the conclusion of the routine.

20 Upon completion of step 202, the routine transitions to query step 203, which compares the comparison entry currently stored in the "this\_entry" field with the originally received number (stored in the "number" field), on a digit-by-digit basis, to determine whether  
25 the currently examined comparison entry more closely matches the originally received number than any previous comparison entry listed in the template.

09931047 101601

To this end, a numerical value (e.g., 1) may be assigned for each match of a respective digit; where there is no match, a value of 0 is assigned for that digit. In order for the originally received number to "match" the comparison entry of interest, there must be a one-for-one identity of all of the digits of the two numbers, except for wild card digits, which are ignored. Otherwise, a no match condition for that comparison entry is declared. In addition, step 203 is designed to resolve conflicts between various types of wild cards; X (digits 0-9), N (digits 2-9) and \$ (any number of characters), by prioritizing the wild cards as follows:  $N=X>\$$ .

In a preferred embodiment, if each matching digit has a value of '1', the \$ is given a value of  $-1/2$ . In this case, therefore, the priority is as follows: 'matching digit'  $> N = X > \$ > -$  'matching digit', so that '1'  $> 0 = 0 > -1/2 > -1$ . Therefore, count values associated with the following matches for the non-limiting examples may be derived: for 963-7938, the count total = 7; for 963-79XX, the count total = 5; for 963-79NX, the count total = 5; for 1-NXX-XXX-XXXX, the count total = 1; for 1\$, the count total =  $1/2$ ; for 963-79\$, the count total = 4.5.

Thus, using a value of '1' per digit match, for a seven digit number with no wild cards (\$, N or X), the comparison total must equal seven for a match to have occurred. If one or more wild card digits is present, the digit match total will be less. As a non-limiting

09981047 101501

illustration, each of comparison entries 123-456X 123-45XX (where X is any digit from 0-9) may be said to "match" the original number 123-4567, since the wild card digits X are ignored. However, the comparison entry 123-456X 'more closely' matches the original number 123-4567, than does the comparison entry 123-45XX, as it produces a larger match value (six digits versus five, for the present example).

Where the currently examined comparison entry more closely matches the originally received number than any previous comparison entry listed in the template, the answer to query step 203 is YES, and the routine steps to step 204. In step 204, the "best\_match\_entry" field is loaded with the comparison entry in the "this\_entry" field, and the routine steps to step 205. On the other hand, if the currently examined comparison entry does not more closely match the originally received number than any previous comparison entry, the answer to query step 203 is NO, and the routine branches to step 205.

In step 205, the "this\_entry" field is loaded with the next comparison entry in the number substitution template, and the routine steps to query step 206. In query step 206, the contents of the "this\_entry" field are examined to determine whether the last comparison entry in the number substitution template has been reached (represented by a null value for that entry). If not, the answer to query step 206 is NO, and the routine

loops back to step 203 and repeats the step and compare sequence, described above.

Eventually, after examination of all of the comparison entries of the number substitution template  
5 (which may contain any number of replacement numbers), the last entry (zero) will be reached, causing the answer to query step 206 to be YES, whereupon the routine transitions to query step 207.

In query step 207, the contents of the  
10 "best\_match\_entry" field are examined for the presence of a null or all zeroes value. As long as one of the comparison entries of the number substitution template has produced a match with the original number (currently stored in the "number" field), then step 204 will have  
15 placed that comparison entry in the "best\_match\_entry" field, making the contents of the "best\_match\_entry" field non-zero, so that the answer to query step 207 is NO. In this case, the routine transitions to step 208.

In step 208, the originally received number contents  
20 of the "number" field are replaced by that one of the output or substitute number entries of the template whose associated comparison entry has produced the best match (currently loaded in the "best\_match\_entry" field). The routine then steps to step 209, wherein the substitute  
25 number is forwarded to the associated device output port.

On the other hand, if no comparison entry in the number substitute template matches the original number, the contents of the "best\_match\_entry" field are zero,

09981047-101501

09981047-101501  
T09707-21078660

and the answer to query step 207 is YES. In this case, the routine branches directly to step 209, wherein the originally received number of the "number" field (rather than a substitute number) are forwarded to the associated IAD output port.

In order to facilitate an appreciation of the functionality of the number substitution routine of the present invention, non-limiting examples of number substitution templates that may be employed by the processing routine of the invention will now be described with reference to the steps of Figure 2.

#### SUBSTITUTION TEMPLATE EXAMPLES

1 - SINGLE NUMBER SUBSTITUTION (ORIGINAL NUMBER = 987-5678; SUBSTITUTE NUMBER = 334-9876)

In the case of a single number substitution, all of the digits of the received original number must match those of a given comparison entry of the template. If there is a one-for-one match of all digits of these two numbers, the comparison entry's substitute or output number will be replaced for that of the original number. Otherwise, the original number will be unmodified. Thus, for the above-listed original number of the present example, the originally received number must match the comparison entry 987-5678 of the accessed number substitution template. If so, the comparison entry's associated substitute number 334-9876 will be substituted

for the original number. Otherwise, the digits of the original number 987-5678 will be forwarded 'as-is'.

Referring now to Figure 2, at step 201, the digits of the original number are received and captured. Next, 5 in step 202, the routine calls up from memory a number substitution template containing the comparison entry (987-5678) and its associated 'to-be-substituted' number (334-9876). In addition, the "number" field is loaded with the originally received number, the "this\_entry" 10 field is loaded with a first comparison entry (here 987-5678) of the template, and the "best\_match\_entry" field is cleared (to all zeroes).

Upon completion of step 202, the routine transitions to query step 203, which compares the comparison entry in 15 the "this\_entry" field with the originally received number (in the "number" field), to determine whether the comparison entry more closely matches the originally received number than any previous comparison entry. For the present example, the template contains only one entry 20 (987-5678). Therefore, if the contents of the received number is exactly 987-5678, then the answer to query step 203 will be YES and, in step 204, the currently examined template entry ('this\_entry' = 987-5678) will be written into the 'best\_match' entry field. However, if the 25 contents of the "number" field (the originally received number) do not match the number: 987-5678, the answer to query step 203 will be NO, and there will be no change of





09921047-101601

On the other hand, if the comparison entry in the number substitute template does not match the original number, namely, the received number is some number other than 987-5678, the contents of the "best\_match\_entry" field will be zero, and the answer to query step 207 is YES. In this case, the routine branches directly to step 209, wherein the originally received number of the "number" field (rather than a substitute number) are forwarded to the associated IAD output port.

10            2 - RANGE OF SUBSTITUTE NUMBERS (444-5600...444-5699) REPLACING RANGE OF ORIGINAL NUMBERS (555-1200...555-1299)

15            The entry in the template would be 555-12XX, 444-56XX; this would automatically present the two ranges to the substitute template logic. In the present example of a range of one hundred substitute numbers, if a received number matches any number within the given range of comparison number entries (here 555-1200...555-1299) of the template, then a substitute number taken from the

20            range of substitute numbers (444-5600...444-5699) uniquely associated with that entry will be replaced for that of the original number. Otherwise, the original number will be unmodified. Thus, for example, for the above-listed range, originally received numbers 555-1201,

25            555-1234, and 555-1278 will be replaced by associated substitute numbers in the replacement range as 444-5601, 444-5634, and 444-5678, respectively.

Referring again to Figure 2, at step 201, the digits of the original number are received and captured. For purposes of a non-limiting example, the received number will be the number 555-1288. In step 202, the routine  
 5 calls up from memory the substitution template containing the above substitution range, including each of the 100 comparison entries (555-1200...555-1299) and their respectively associated 'to-be-substituted' numbers (444-5600...444-5699). Also, the "number" field is loaded with  
 10 the originally received number (here 555-1288), the "this\_entry" field is loaded with a first comparison entry (e.g., 555-1200) of range contained in the template, and the "best\_match\_entry" field is cleared (to all zeroes).

15 Upon completion of step 202, the routine transitions to query step 203, which compares the first comparison entry (555-1200) in the "this\_entry" field with the originally received number (555-1288) stored in the "number" field), to determine whether the comparison  
 20 entry more closely matches the originally received number than any previous comparison entry. For the present example, these two values do not match, so that the answer to query step 203 is NO, and there is no change of the contents (currently zero) of the 'best\_match' entry  
 25 field.

Next, in step 205, the "this\_entry" field is loaded with the next comparison entry in the number substitution template (555-1201, in the present example), and the

09981047-101601

routine steps to query step 206. Since the next entry is not all zeroes, indicating that the end of the comparison entries of the substitution template has not been reached. The answer to query step 206 is therefore NO,  
5 and the routine loops back to step 203.

This iterative process is repeated for the next 87 comparison entries in the template until step 203 detects a match between the value 555-1288 that has been loaded into "this\_entry" field and the same number in the  
10 "number" field. When this happens, the answer to step 203 will become YES, and in step 204, the current comparison entry 555-1288 in the "this\_entry" field is written into the 'best\_match' entry field. The iterative routine then continues through the remaining comparison entries in the  
15 template (555-1289...555-1299), none of which matches the original number.

Eventually, the last entry (zero) of the substitution template will be reached, causing the answer to query step 206 to be YES, and the routine transitions  
20 to query step 207. In query step 207, the "best\_match\_entry" field is examined for the presence of an all zeroes value. Since the originally received number exactly matches the comparison entry (555-1288), that comparison entry is currently stored in the  
25 "best\_match\_entry" field, making the contents of the "best\_match\_entry" field non-zero, so that the answer to query step 207 will be NO, and the routine transitions to step 208. In step 208, the originally received number

contents of the "number" field (555-1288) are replaced by  
the substitute number entry (444-5688), and the routine  
steps to step 209, wherein the substitute the number  
(444-5688) is forwarded to the associated device output  
5 port.

3 - TEMPLATE CONTAINING MULTIPLE NUMBER RANGES  
(SINGLE NUMBER SUBSTITUTION (ORIGINAL NUMBER = 987-5678;  
SUBSTITUTE NUMBER = 334-9876) AND RANGE OF SUBSTITUTE  
NUMBERS (444-5600...444-5699) REPLACING RANGE OF ORIGINAL  
10 NUMBERS (555-1200...555-1299))

In this example, there are two template entries: 1)  
987-5678 334-9876; and 2) 555-12XX 444-56XX. This third  
example is a combination of the first and second  
examples, described above. Here, the template contains  
15 two comparison entry ranges, a first of which contains a  
single number 987-5678 having an associated substitute  
number 334-5678, and the second of which contains 100  
comparison entries 555-1200...555-1299 having  
respectively associated numbers 444-5600...444-5699. In  
20 this example, if a received number matches either the  
number 987-5678 (the lone comparison number of the first  
range), or any of the comparison number entries (here  
555-1200...555-1299) of the second range, then a  
substitute number uniquely associated with the matched  
25 entry will be replaced for that of the original number,  
as described above in examples 1 and 2. Otherwise, the  
original number will be sent unmodified.

4 - MODIFICATION OF LENGTH/COMPOSITION OF ORIGINAL  
NUMBER BY ADDING A PREFIX (E.G., AREA CODE) TO AN  
ORIGINAL NUMBER

In this example, the template is configured as 555-  
5 12XX 256-444-56XX. This fourth example illustrates the  
use of the number substitution template of the invention  
to automatically prepend a prefix, such as an area code,  
or a one plus the area code, to an original number. A  
non-limiting example of where this scheme is particularly  
10 useful involves applications, such as interstate urban  
environments, where dialing requirements have been  
augmented to require all calls, including local calls, to  
include the called number's area code, in addition to the  
customary seven digit number. To this end, the template  
15 of the present example contains a seven digit range of  
comparison entries, respective ones of which have a seven  
digit range of ten digit substitute numbers, and the  
first three digits of each of which corresponds to a  
prepended area code.

20 For purposes of a reduced complexity, non-limiting  
illustration, consider the one-hundred number range of  
the second example, described above. For this example,  
the prepending template of the fourth example also  
contains the comparison entries 555-1200...555-1299.  
25 However, its respectively associated substitute numbers  
is the one-hundred ten digit substitute number set: 256-  
444-5600...256-444-5699, where 256 is the prepended area  
code.

09981047 101501

Namely, if the original number matches any of the seven digit comparison number entries (here 555-1200...555-1299), then a substitute ten digit number having the prefix 256, plus the seven digits uniquely associated with the matched entry will be substituted for the original number, in the same manner described above for the second example. Otherwise, the original number will be sent unmodified. Thus, originally received seven digit numbers 555-1201, 555-1234, and 555-1278, for example, will be replaced by associated ten digit substitute numbers 256-444-5601, 256-444-5634, and 256-444-5678, respectively.

#### 5 - REMOVING PREFIX (E.G., 1) FROM ORIGINAL NUMBER

The template for this example is: 1-256-555-12XX 256-444-56XX. This fifth example illustrates the use of the number substitution template of the invention to automatically remove or excise a number, such as a long distance '1' digit from the front end of an original number, such as from a ten digit number that uses the area code but is not tariffed as a long distance call, eliminating the use of the precursor '1'. In this case, the template contains a ten digit range of comparison entries, the first digit of which is the precursor '1', and respective ones of which have an eleven digit range of ten digit substitute numbers, comprised of the area code followed by a seven digit number.

Again, as a reduced complexity, non-limiting

09981047-101601

illustration, consider the one-hundred number range of the second example, described above, each number of which also includes a three digit area code prepended by a '1' digit. For this example, the excising template of the fifth example contains a set of 100, eleven digit comparison entries 1-256-555-1200...1-256-555-1299, respectively associated substitute numbers of which is the one-hundred ten digit substitute number set: 256-444-5600...256-444-5699.

10        Thus, if the original number matches any of the eleven digit comparison number entries (here 1-256-555-1200...1-256-555-1299), then a substitute ten digit number having the prefix 256, plus the seven digits uniquely associated with the matched entry will be substituted for the original number, in the same manner described above for the fourth second example. Otherwise, the original number will be sent unmodified. Thus, originally received seven digit numbers 1-256-555-1201, 1-256-555-1234, and 1-256-555-1278, for example, will be replaced by associated ten digit substitute numbers 256-444-5601, 256-444-5634, and 256-444-5678, respectively, from each of which the precursor '1' has been removed.

6 - MULTIPLE DIFFERENT SUB-RANGES OF SUBSTITUTE NUMBERS (444-5600...444-5629; 334-6740...334-6749; 444-5640...444-5699) REPLACING RESPECTIVE SUB-RANGES (555-1200...555-1229; 555-1230...555-1239; 555-1240...555-1299) WITHIN COMMON RANGE OF ORIGINAL NUMBERS (555-



1200...555-1299)

09981047-101501

This template has two entries: 1) 555-12XX 444-56XX; and 2) 555-123X 334-674X. This example is a derivative of the second example containing a range of  
5 original numbers having respective subsets or subranges that are to be replaced by associated substitute numbers falling in multiple (e.g., two) subranges or sets. In the present example, if a received number matches any number within the overall range of comparison number entries  
10 (here 555-1200...555-1299) of the template, then a substitute number taken from one of the above-listed subranges of substitute numbers (444-5600...444-5629; 334-6740...334-6749; 444-5640...444-5699) associated with the subrange containing the comparison entry will be replaced  
15 for original number. Otherwise, the original number will be unmodified.

Thus, for the above-listed sub-ranges, originally received numbers 555-1201 and 555-1278 falling within the subrange of numbers (555-1200...555-1229 and 555-  
20 1240...555-1299) within the overall range of numbers (555-1200...555-1299) will be replaced by respective substitute numbers 444-5601 and 444-5678, whereas an originally received number 555-1235 within the subrange of numbers (555-1230...555-1239) of the overall range of  
25 numbers (555-1200...555-1299) will be replaced by the substitute number 334-6745. These template replacement relationships may be expressed as: 555-12XX ==> 444-56XX, and 555-123X ==> 334-674X.

09934047-101501  
TOTAL 24073600

It should be noted that the two subranges of the template have different code resolutions. The comparison entry subrange 555-12XX has a five digit resolution, while the comparison entry subrange 555-123X has a six digit resolution. In the course of execution of the routine of Figure 2, a 'best\_match' entry for an original number 555-1234 would produce a match value of five from the lower resolution subrange 555-12XX (five exactly matching digits (55512), but would produce a match value of six from the higher resolution subrange 555-123X (six exactly matching digits (555123). Therefore, when the answer to query step 206 is YES (all comparison entries in the template have been processed), step 204 will have loaded the 'best\_match\_entry' field with the higher resolution range comparison entry 555-1234 producing the larger valued match (six vs. five digits), whose associated substitute number is the number 334-6734. Consequently, the substitute number will be the number 334-6734.

20           7 - MULTIPLE MODIFICATIONS OF MULTIPLE ORIGINAL NUMBERS

This seventh example illustrates the use of the number substitution template of the invention to perform a variety of modifications of different ranges, lengths and formats of original numbers. For example, in the case of an outgoing call to the PSTN, the service provider may require that it always receive ten digits, including area

09981047 101501  
109907 24078550

code, even in the case of a local call. The template-based routine of the invention allows a calling party, who may be accustomed to dialing only seven digits for a local call, to continue to do so, with one or more  
5 prepended codes, such as an area code, an access or 'PIC' code associated with a CLEC, and the like, to be automatically provided by the template. In this case, the prepended code is not part of the digit comparison. In a complementary manner, the template provides for  
10 selectively ignoring one or more digits of the originally received number, such a precursory '1' used to initiate a long distance call.

In the present example, the template is to perform the following substitutions.

15 A- Any original (local seven digit) number in the range of 200-0000 through 999-9999 is to be prepended with the area code 256 and thereby translated to a corresponding number within the ten digit number range 256-200-0000 through 256-999-9999. Here, the template  
20 entry is NXX-XXX 256=NXX-XXX.

B- However, if the original digits are '911' (corresponding to an emergency call, but falling within the subrange 911-0000...911-9999 within the above range 200-0000...999-XXXX), then those same digits '911' are to  
25 be sent 'as is'. The template entry is: 911 911.

C- Any (eleven digit long distance) original number in the range 1-205-200-0000 through 1-205-999-9999 is to have the precursor '1' excised to yield a corresponding

number in the ten digit number range 205-200-0000 through 205-999-9999. The template entry is: 1-205-NXX-XXXX 205-NXX-XXXX.

D- Any original number \$ (where \$ = of any number of 5 characters), that begins with a '1' and does not fall within the previous number set (1-205-200-0000 through 1-205-999-9999), is to be modified so that its precursor code is '10103211' rather than '1'. The template entry is: 1\$ 10103211\$.

10 E- However, if the original number is the number '1411' (local directory assistance in some localities and falling within the set 1\$), then that number (1411) is to be translated to the seven digit (local directory assistance) number '555-1212'. The template entry is:  
15 1411 555-1212.

Case A is handled in the same manner as the prepending of the area code of the fourth example, and can be expressed as the translation NXX-XXXX ==> 256-NXX-XXXX (where N is any digit from 2-9). However, because  
20 the emergency call number (911) of case B falls within the range of original numbers of case A, there is a potential conflict. The routine of Figure 2 readily resolves this potential conflict in favor of case B, in the manner of the sixth example, described above, since  
25 case B has a greater code resolution (three digits (911) than case A (which has no resolution).

Namely, in the course of execution of the routine of Figure 2, a 'best\_match' entry for an original number

09981047-101601

911-1234 would produce a match value of zero from the lower resolution subrange NXX-XXXX, but would produce a match value of three from the higher resolution subrange 911 (three exactly matching digits (911)). Therefore, when  
5 the answer to query step 206 is YES (all comparison entries in the template have been processed), step 204 will have loaded the 'best\_match\_entry' field with the higher resolution range comparison entry 911 producing the larger valued match (three vs. zero digits), whose  
10 associated substitute number is the number 911. Thus, the emergency code 911 will be sent.

Case C is handled in the same manner as the excising of the area code of the fifth example, and can be expressed as the translation 1-205-NXX-XXXX ==> 205-NXX-  
15 XXXX. However, because an original number of case C may fall within the range of original numbers of case D, there is a potential conflict. The number substitution routine of Figure 2 resolves this potential conflict in favor of case C, since a range of characters is given  
20 priority in step 203, in the case of a match conflict with wild cards N and X, as described previously. As a consequence, once all comparison entries have been processed (the answer to query step 206 is YES), step 204 will have loaded the 'best\_match\_entry' field with the  
25 higher priority entry 1-205-NXX-XXXX, whose associated substitute number is the number 205-NXX-XXXX. Therefore, the number substitute 1010321\$ will be sent.

09981047-101501  
TOSTOT 240TB60

The conflict between Case E and case D is handled by step 203 in substantially the same manner as the conflict between case B and case A, described above. Namely, the routine of Figure 2 resolves the conflict in favor of case E, in the manner of the sixth example, described above, since case E has a greater code resolution (four digits (1411) than case D (which has a code resolution of one digit (1)). Therefore, once all comparison entries have been processed (the answer to query step 206 is YES), step 204 will have loaded the 'best\_match\_entry' field with the higher priority entry 1411, whose associated substitute number is the number 555-1212. Therefore, the substitute number 555-1212 will be sent.

As noted above, each of the digits of an original number may be compared with a corresponding digit of successive template entries or accommodate wild card digits (\$, N, X). Advantageously, as the number substitution mechanism of the invention is software-based, it provides considerable flexibility in processing received digits of an original number and the replacement digits of a substitute number. Thus, as can be seen from the foregoing examples, it is not necessary to compare all of the digits of the two numbers, and the number of digits in the originally received number need not be the same as that of the template substitute number that is to be forwarded to a downstream path. Either number could have more or less digits than the other.

09981047-101501

Also, the manner in which the substitute number is forwarded over the outgoing path of interest may be readily defined in accordance with number processing requirements of the called circuit. Thus, the substitute  
5 number entry may include one or more control flags (such as pause 'commas') embedded with the number contents of the template, to provide for staggered transmission or 'fragmented' transport of the contents substitute number. This allows a calling party, upon initially placing a  
10 call, to enter one or more auxiliary numeric digits (such as an extension number) without having to wait for a prompt (such as that provided by an automated attendant) for such digits by the destination circuit, and thus provide for automatic extension dialing.

15 As will be appreciated from the foregoing description, the telephone number substitution mechanism of the present invention is readily incorporatable into the call-routing software of a microcontroller of a customer premises-installed communication device, so as  
20 enable the digits of an original telephone number to be automatically modified or replaced as necessary, to conform with the connectivity requirements of the communication link serving a destination device. As a result, the invention provides a user friendly mechanism  
25 to accommodate changes to the telephone numbers and number formats employed by either a PSTN infrastructure or those of customer premises equipment, without having

to reconfigure equipment at either a (central office)  
switch or the customer site.

While we have shown and described an embodiment in  
accordance with the present invention, it is to be  
5 understood that the same is not limited thereto but is  
susceptible to numerous changes and modifications as  
known to a person skilled in the art, and we therefore do  
not wish to be limited to the details shown and described  
herein but intend to cover all such changes and  
10 modifications as are obvious to one of ordinary skill in  
the art.

09981047-101601